

## Quick Reference

This is a quick reference of the major specifications for each class.

### Can-Am



- **Total Weight** = 100 grams minimum
- **Chassis Width** = 3.125" maximum
- **Body Width** = 3.250" at the wheel arches
- **Body Thickness** = .010" with .007" minimum on sides
- **Track Width, F & R** = 3.125"
- **Chassis Clearance, F & R** = .015" / .050" minimum
- **Front Tire Diameter** = .750" minimum
- **Front Tire Width** = .225" minimum
- **Rear Tire Diameter** = .8125" minimum
- **Rear Tire Width** = .810" maximum
- **Motor Type** = PS4002B, PS4002B-B, Topline or JK Falcon 7, JK Hawk Retro FK, TSR D3, Slick 7
- **Gears** = Production only; no modifications except sanding diameter
- **Body Height** = 1.375" maximum
- **Front Grille** = .063" (1/16") except Ti22
- **Spoiler Size / Height** = no wider than body; .500" maximum
- **Driver Figure / Interior** = Fully molded, minimum two-color, presentably / realistically painted, no paper interiors

### GT Coupe - PD



- **Total Weight** = 110 grams minimum
- **Chassis Width** = 3.125" maximum
- **Body Width** = 3.250" at the wheel arches
- **Body Thickness** = .010" with .007" minimum on sides
- **Track Width, F & R** = 3.125"
- **Chassis Clearance, F & R** = .015" / .050" minimum
- **Front Tire Diameter** = .750" minimum
- **Front Tire Width** = .225" minimum
- **Rear Tire Diameter** = .8125" minimum
- **Rear Tire Width** = .810" maximum
- **Motor Type** = PS4002B, PS4002B-B
- **Gears** = Production only; no modifications except sanding diameter
- **Body Height** = 1.375" maximum
- **Front Grille** = .063" (1/16")
- **Spoiler Size / Height** = no wider than body; .500" maximum
- **Rear Window** = Painted, tinted, or covered with interior.
- **Driver Figure / Interior** = Fully molded, minimum two-color, presentably / realistically painted, no paper interiors

### Formula 1



- **Total Weight** = 100 grams minimum
- **Chassis Width** = 1.625" maximum
- **Body Width** = 1.685" excluding front wings if present
- **Minimum Wheelbase** = 3.875"
- **Maximum Wheelbase** = 4.250"
- **Body Thickness** = .010 with .007 minimum on sides
- **Track Width, F & R** = 3.250"
- **Chassis Clearance, F & R** = .015" / .050" minimum for major events; .040" rear if regionally allowed along with .790" tire
- **Front Tire Diameter** = .750" minimum
- **Front Tire Width** = .375" minimum
- **Rear Tire Diameter** = .8125" minimum for major events; .790" if regionally allowed along with .040" rear clearance
- **Rear Tire Width** = .810" maximum
- **Motor Type** = PS4002B, PS4002B-B, Topline or JK Falcon 7, JK Hawk Retro FK, TSR D3, Slick 7
- **Gears** = Production only; no modifications except sanding diameter
- **Body Height, Lotus 49 style** = 1.375" maximum
- **Front Wings, Lotus 49 style** = Width across front wings 2.875" maximum.
- **Body Height, All Others** = 1.125" maximum
- **Front Grille** = .125" (1/8")
- **Driver Figure / Interior** = Fully molded, minimum two-color, presentably / realistically painted, no paper interiors

### GT Coupe - FK




- **Racer Eligibility** At IRRA™ Premier events, racers on the IRRA™ "GTC-PD Only" list may enter *only* GTC-PD races. Racers not on the that list may enter both GTC-FK and GTC-PD.
- **Total Weight** = 110 grams minimum
- **Chassis Width** = 3.125" maximum
- **Body Width** = 3.250" at the wheel arches
- **Body Thickness** = .010" with .007" minimum on sides
- **Track Width, F & R** = 3.125"
- **Chassis Clearance, F & R** = .015" / .050" minimum
- **Front Tire Diameter** = .750" minimum
- **Front Tire Width** = .225" minimum
- **Rear Tire Diameter** = .8125" minimum
- **Rear Tire Width** = .810" maximum
- **Motor Type** = Topline or JK Falcon 7, JK Hawk Retro FK, TSR D3, Slick 7
- **Gears** = Production only; no modifications except sanding diameter
- **Body Height** = 1.375" maximum
- **Front Grille** = .063" (1/16")
- **Spoiler Size / Height** = no wider than body; .500" maximum
- **Rear Window** = Painted, tinted, or covered with interior.
- **Driver Figure / Interior** = Fully molded, minimum two-color, presentably / realistically painted, no paper interiors

## Stock Car



- **Total Weight** = 120 grams minimum
- **Chassis Width** = 3.00" maximum
- **Wheelbase** = 4.50" minimum
- **Guide Lead** = .750
- **Body Width** = 3.250" at the wheel arches
- **Body Thickness** = .015 with .010 minimum on sides
- **Track Width, F & R** = 3.00" maximum
- **Chassis Clearance, F & R** = .050" / .050" minimum
- **Tire Diameter, F & R** = .8125" maximum
- **Front Tire Width** = .375" minimum
- **Rear Tire Width** = .810" maximum
- **Motor Type** = Topline or JK Falcon 7, JK Hawk Retro FK, TSR D3, PS4002, Slick 7
- **Gears** = Production only; no modifications except sanding diameter
- **Driver Figure / Interior** = Fully molded, minimum two-color, presentably / realistically painted, no paper interiors

## Retro Anglerwinder



- **Total Weight** = 100 grams minimum
- **Chassis Width** = 3.125" maximum
- **Body Width** = 3.250" at the wheel arches
- **Body Thickness** = .010" with .007" minimum on sides
- **Track Width, F & R** = 3.125"
- **Chassis Clearance, F & R** = .015" / .050" minimum
- **Front Tire Diameter** = .750" minimum
- **Front Tire Width** = .225" minimum
- **Rear Tire Diameter** = .790" minimum
- **Rear Tire Width** = .810" maximum
- **Motor Type** = PS 4002B, PS4002B-B, Topline or JK Falcon 7, JK Hawk Retro FK, TSR D3, Slick 7
- **Body Height** = 1.375" maximum
- **Front Grille** = .063" (1/16") except Ti22
- **Spoiler Size / Height** = no wider than body; .500" maximum
- **Driver Figure / Interior** = Fully molded, minimum two-color, presentably / realistically painted, no paper interiors. The rear window must be painted, tinted, or covered with interior on GTC bodies